

MOTOR OIL 5w/40

PERFORMANCE PROFILE

API SL/CF MB 229.3 VW502.00/505.00
ACEAA3/B3

APPLICATION

A high performance synthetic multi grade gasoline engine oil formulated from premium quality synthetic base oils and selected additives. It is recommended for all modern gasoline engines and provide excellent protection from combustion deposits, heat induced oil oxidation and sludge deposits. It can be used for petrol engines with normal four stroke valve and turbo type with or without catalyts.



KEY FEATURES

- Exceptional thermal stability at high temperature
- Protection from the most severe weather conditions.
- Extremely high control over wear, rust and corrosion to ensure long life of moving parts.
- Outstanding lubrication powers in all seasons
- Maximum shear stability
- Longer maintenance intervals and oil change period
- Easy starting in extremely cold weather.
- Excellent protection against oxidation, foaming, low temperature sludge and high temperature deposits
- Reduce fuel consumption and exhaust emission.

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	TYPICAL VALUE
		5W-40
Density at 15 C, Kg/L	ASTM D1298	0.884
Viscosity at 100 C, cSt	ASTM D445	14.5
Viscosity Index	ASTM D2270	174
Flash Point, COC, C	ASTM D92	236
Pour Point, C	ASTM D97	-36

